

Round Tapered Aluminum Poles (RTAP) - Base Mounted

Catalogue #	Pole Height ft.	Pole Taper in.	Anchor Bolt Dia. In.
5" Diameter Poles			
RTAP15-535-AB	15	5 - 3 1/2"	3/4" x 24"
RTAP20-535-AB	20	5 - 3 1/2"	3/4" x 24"
RTAP25-535-AB	25	5 - 3 1/2"	3/4" x 24"
RTAP30-535-AB	30	5 - 3 1/2"	3/4" x 24"
6" , 7" and 8" Diameter Poles			
RTAP20-645-AB	20	6 - 4 1/2"	3/4" x 24"
RTAP20-745-AB	20	7 - 4 1/2"	1" x 30"
RTAP20-845-AB	20	8 - 4 1/2"	1" x 30"
RTAP25-745-AB	25	7 - 4 1/2"	1" x 30"
RTAP25-845-AB	25	8 - 4 1/2"	1" x 30"
RTAP30-845-AB	30	8 - 4 1/2"	1" x 30"
RTAP35-845-AB	35	8 - 4 1/2"	1" x 30"
RTAP35-1060-AB	35	10 - 6"	1 1/4" x 42"
RTAP40-1060-AB	40	10 - 6"	1 1/4" x 42"

Notes:

*Aluminum wall thickness denoted by;

B- 0.156" THK

C- 0.188" THK

E- 0.250" THK

For Direct Burial, substitute "AB" for "DB" in catalogue number,

All poles are complete with hand hole cover and ground lug,

All base mounted poles are complete with galvanized steel anchor bolts, 2 nuts, 2 washers,

Pole are standard Rotary Polish Finish. Powder coating available at an additional cost,

Pole Material: Aluminum

Anchor Bolts Steel : 44 kpsi Min. Yield

Welding Conforms to CSA W47.1 and W47.2